

W-24VAC-18P/10A

Camera Power Supply



Model

W-24VAC-18P/10A

Features

- > Input 110/120 VAC
- > Output 24V DC , 18channels
- > 10 Amp Supply Current
- > Integral Surge Protection
- > Individual LED Power Indication
- > Individual PTC Output Protection
- > Max. Amp: 1.1Amp/ch

W-24VAC-18P/10A

Specifications

Model	W-24VAC-18P/10A	
Specification	240W24V10A18P	
Shape Dimension	28×20.8×8.7cm	
Weight	4.78kg	
Input	Input Voltage	110/120VAC
	Input Voltage Frequency	60Hz
Output	Output Voltage	24VAC±5%
	Output Current	10A , 18channels for 18sets load
Fuse	Type /Rating	PTC 1.1A/60V
Protection	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when condition removed, then switch back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will open the circuit, when condition removed, PTC fuse will automatically back to close.
Circumstances	Working Temperature	0℃ ~ +40℃
	Storage temperature	-20℃ ~ +85℃
	RH	5% ~ 95%
	Heat release	Natural heat dissipation
Connection	Input	three-pin socket
	Output	18channels output

*Design and specifications are subject to change without notice.