

W-24VAC-9P/5A

Camera Power Supply



Model

W-24VAC-9P/5A

Features

- Input 110/120 VAC
- Output 24V DC , 9channels
- 5 Amp Supply Current
- Integral Surge Protection
- Individual LED Power Indication
- Individual PTC Output Protection
- Max. Amp: 1.1Amp/ch

W-24VAC-9P/5A

Specifications

Model	W-24VAC-9P/5A	
Shape Dimension	24.5×20.8×8.7cm	
Weight	4.04kg	
Input	Input Voltage	110/120VAC
	Input Voltage Frequency	60Hz
Output	Output Voltage	24VAC±5%
	Output Current	5A , 9 channels for 9 sets load
Fuse	Type /Rating	PTC 1.1A/60V
Protection	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when clearing of fault, it switches back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will break the circuit, when clearing of fault, it switch back to normal automatically.
Circumstances	Working Temperature	0℃ ~ +40℃
	Storage temperature	-20℃ ~ +85℃
	RH	5% ~ 95%
	Heat release	Natural heat dissipation
Connection	Input	Three-pin socket
	Output	9channels output

*Design and specifications are subject to change without notice.