GSS

2 Wire Distributor

Instruction

There are a large number of 2-wire wiring buildings around the world. With the help of DNAKE 2-wire Distributor 290A, any apartments with old intercom system can be upgraded to IP system with no cable replacement.

Key Features

- Convert 2-wire to ethernet connection
- Two Ethernet Ports
- Support up to 8 indoor monitors

Physical

- Material: Plastic
- Power Supply: DC 48V ±10%
- Rated Power: 4 W
- Wire Diameter: RVV 2*0.75, ≤100m
- Network Cable: Cat 5e, Cat 6 or better
- Ethernet Port: 2 x RJ45, 10/100 Mbps adaptive
- Main In: 1
- Main Out: 1
- Access Mode: CSMA/CA
- Transmission Scheme: Wavelet OFDM
- Frequency Bandwidth: 2 MHz to 28 MHz
- Dimension: 197 x 114 x 38 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -10°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

Package Features

- Package Content:
  - DNAKE 290A
    (Power adapter included)
- Qty/CTN: 20 pcs
- N.W/PCS: 0.27 kg
- G.W/CTN: 7.48 kg
- Giftbox Size: 210 x 115 x 52 mm
- Carton Size: 450 x 480 x 285 mm