

5MP OEM WIFI DOOR BELL



- 1/2.7-in. 5 MP Progressive-scan CMOS Sensor
- Dual-band WiFi, IEEE802.11a/b/g/n/ac, 2.4 GHz and 5 GHz options
- H.265 and H.264 Dual Video Compression
- 2560 x 1920 at 15 fps Maximum Resolution
- 2.2 mm Fixed Lens
- Built-in Microphone and Speaker for Real-time Communication
- Motion Detection with Human Detection
- Built-in White-light Illuminator for Visual Deterrence
- Maximum IR LED Length 5.0 m (16.50 ft)
- Five-year Warranty*

System Overview

The 5MP WiFi Video Doorbell is a component of the IPC-WDB5MP residential series. The doorbell offers specialized motion detection that distinguishes humans from other objects, and transmits video and audio to a mobile device for remote visual confirmation and communication with visitors. This device is compatible with NVRs; X5, X7, and X82 Series HDCVI DVRs, and with the DMSS mobile application.

Technical	Specification	
iccillical	Specification	

Camer	a
-------	---

Image Sensor	1/2.7-in. 5MP CMOS
Effective Pixels	2560 x 1920
RAM/ROM	256 MB / 128 MB
Electronic Shutter Speed	Auto/Manual 1/3 s to 1/100,000 s
Scanning System	Progressive
IR Distance	5.0 m (16.50 ft)
IR Control	Automatic
IR Illuminator	Two (2) LEDs
White-light Illuminator	Built-in, programmable
Built-in Battery	200 mAh Lithium Battery
Lens	

Lens

Lens Type	Fixed-focal
Lens Mount	M8
Focal Length	2.2 mm
Maximum Aperture	F2.0
Angle of View	Horizontal: 124° Vertical: 92° Diagonal: 164°
Iris Control	Fixed

DORI Distances¹

Detect	Observe	Recognize	Identify
(8 ppf)	(19 ppf)	(38 ppf)	(76 ppf)
44.0 m	17.60 m	8.80 m	4.40 m
(144.36 ft)	(57.74 ft)	(28.87 ft)	(14.44 ft)

Video

Video Compression		H.265, H.264
	High	2560 x 1920 at 15 fps
Resolution	Medium	1440 x 1080 at 15 fps
	Low	640 x 480 at 15 fps
Streaming Capa	bility	Two (2) Streams
Frame Rate	Main Stream	2560 x 1920 at 15 fps
riaille Rate	Sub Stream	640 x 480 at 15 fps
Video Bit Rate		H.264: 32 kbps to 8192 kbps H.265: 32 kbps to 8192 kbps
Day/Night		Auto (ICR), Color, B/W
WDR		Digital WDR
Optical Features		White Balance, Smart Illumination
Noise Reduction		3D NR
Motion Detection		On, Off
Audio		
Interface		Input: One (1) Built-in Microphone Output: One (1) Built-in Speaker
Two-way Talk		Three (3) built-in pre-recorded messages plus three (3) customized recorded messages
Compression		G.711A, G.711Mu, PCM
Audio Sampling		8 KHz, 16 KHz, 32 KHz

WiFi

	DH-DB6I	DH-DB6I-CAN
2.4 GHz IEEE802.11b/g/n	• 2400 to 2483.5 MHz RF POWER ≤30 dBm	• 2400 to 2483.5 MHz RF POWER ≤30 dBm
5 GHz IEEE802.11a/n/ac	• 5150 to 5350 MHz, 5470 to 5725 MHz RF POWER ≤24 dBm	• 5250 to 5350 MHz 5470 to 5600 MHz 5650 to 5725 MHz RF POWER ≤24 dBm
, ,	• 5725 to 5850 MHz RF POWER ≤30 dBm	• 5725 to 5850 MHz RF POWER ≤30 dBm

Network

Network Protocol	IPv4; IPv6; HTTP;TCP; UDP; ARP; RTP; RTSP; RTCP; DHCP; DNS; DDNS; QoS; NTP; Multicast; ICMP; IGMP
Edge Storage	Micro SD Card Slot, maximum 256 GB
Interoperability	CGI, P2P, SDK, API
Mobile Operating System	IOS, Android
Management Software	DMSS
Compatibility	 Any Dahua NVR Dahua X5, X7, X82 Series HDCVI DVRs Dahua DMSS Mobile Application

Certifications

Electromagnetic	47 CFR FCC Part 15, Subpart B;
Compatibility (EMC)	FCC ID: FCC PART 15C; FCC PART 15E

Electrical

Power Supply ²		12 VDC to 24 VDC or 16 VAC to 24 VAC, 0.8 A USB (5 VDC±5%, 2 A) ²
	5 VDC	Basic: 2.3 W Maximum: 3.3 W
Power Consumption	12-24 VDC	Basic: 2.9 W Maximum: 4.8 W
	16-24 VAC	Basic: 2.9 W Maximum: 4.9 W

Environmental

Operating Temperature	–20° C to +50° C (–4° F to 122° F), Less than 95% RH
Ingress Protection	IP65

Construction

Casing	Plastic
Dimensions (L x W x H)	130.0 mm x 45.0 mm x 22.50 mm (5.12 in. x 1.77 in. x 0.88 in.)
Net Weight	0.11 kg (0.24 lb)
Gross Weight	0.51 kg (1.12 lb)
Installation	Surface-mount

Ordering Information		
Туре	Part Number	Description
WiFi Video Doorbell	IPC-WDB5MP	5MP WiFi Video Doorbell, 2.4 GHz and 5 GHz Wi-Fi connectivity, two-way talk, Available in USA only
	IPC-WDB5MP	5MP WiFi Video Doorbell, 2.4 GHz and 5 GHz Wi-Fi connectivity, two-way talk, Complies to Canadian Regulations
Package Contents	Quick Start Guide (QSG) Video Doorbell Power Kit for Chime (referred to as a Chime Kit in QSG) 32 GB Pre-installed MicroSD Card Wiring Package 15° Horizontal Bracket 5° Vertical Bracket Mounting Kit	

Technical Specifications

mm [inch

