

KB-1200KI

Network Keyboard



Features and Functions

- 128 x 64 screen
- 4-axis joystick
- Connectable to the Multi-functional Video Center (MVC), Matrix Access Gateway (MAG), Video Wall Controller, Decoder, etc.; and shortcut operation of camera/camera groups switch on video wall
- Connectable to dome and realize PTZ control and picture capture by joystick operation
- Connectable to DVR via network or serial port, and operation of front panel buttons
- 16 user accounts management: 1 admin and 15 operators
- System upgrade and import / export of configuration files by USB-flash disk
- Captured pictures(FAT32) can be stored in U-flash disk
- Network access and configuration by Web browser support; and up to 1000 devices can be managed in the keyboard operation mode

Specifications

Model		KB-1200KI
System	LCD screen	128 x 64 pixel screen
	Joystick	4-axis joystick
	Control mode	Network, RS-232, RS-422, RS-485
External Interfaces	Network interface	1; 10 M/100 Mbps self-adaptive Ethernet interface
	Serial interface	1 RS-232, 1 RS-422, 1 RS-485
	USB interface	1 × USB 2.0
General	Power supply	12 VDC
	Consumption	≤ 4.5 W
	Working temperature	-10 to +55°C (14 to 131°F)
	Working humidity	10% to 90%
	Dimensions (W × D × H)	435 × 193 × 110 mm (17.1 × 7.6 × 4.3 inch)
	Weight	≤ 1 kg (2.2 lb)