

PB-AP1900-3

867MBPS ACCESS POINT





Product Overview

PB-AP1900-3 is a 5.8GHz wireless bridge, which can easily complete point-to-point or point-to-multiple devices pairing through DIP switches, no need to log in to the page to set up.

The wireless speed can up to 867Mbps and it can prevent from the weather, dust and the sun with the IP65 protection level shell.

It is mainly used in warehouse, construction site, factory monitoring and other places.

Features

- DIP Settings is more convenient to use
- Easy installation, support pole mounting
- Support PoE 24V Power Supply
- Support IEEE 802.11 b/g/n/ac Protocol
- Wireless Speed Up to 867Mbps
- IP65 Shell Level can Prevent From the Weather, Dust and the Sun
- Excellent Transmitting Power and Receiving Sensitivity



867MBPS ACCESS POINT



PROBE

Product Specification

Chipset	QCA9563+ QCA9886						
DRAM	DDR2 128MByte						
FLASH	16MByte	16MByte					
IC	SKY85728*2						
Wired Port	10/100/1000Mbps LAN*2						
Speed	867Mbps						
Modulation	OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256QAM, DBPSK, DQPSK, CCK						
Standard	IEEE802.11a,IEEE802.11n,IEEE802.3u,IEEE802.11ac						
Channel	5180Mhz~5825Mhz						
Power Dissipation	≤7W						
Power	POE 48V 0.5A						
RF @25℃±2dB	802.11a	6-24Mbps		26±2dBm			
		36-48Mbps		25±2dBm			
		54Mbps		24±2dBm			
	802.11ac		MCS 0-3		26±2dBm		
		HT20	MCS 4		25±2dBm		
			MCS 5		24.5±2dBm		
			MCS 6		24±2dBm		
			MCS 7		23.5±2dBm		
		HT40	MCS 0-3	3	25±2dBm		
			MCS 4		24.5±2dBm		
			MCS 5		24±2dBm		



867MBPS ACCESS POINT



PROBE

					CS 6	23.5±2dBm	
				MCS 0-3		18±2dBm	
				MCS 4		18±2dBm	
		НТ80		MCS 5		18±2dBm	
				MCS 6		18±2dBm	
				MCS 7		16±2dBm	
	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73					
Sensitivity	802.11ac	HT20			MCS 0 ≤ -94; MCS 7 ≤ -76		
		HT40			MCS 0 ≤ -92; MCS 7 ≤ -76		
		HT80			MCS 0 ≤ -90; MCS 7 ≤ -67		
Antenna	Frequency		4900	00 ~ 6100MHz			
	Polarization		Verti	Vertical / Horizon			
	Gain		16DI	16DBi			
Management	WEP Management		Yes	Yes			
	SNMP MIB		Yes				
	Telnet		Yes	Yes			
	Serial Ye		Yes	Yes			
Security	Encryption				WEP 64/128bits,WPA,WPA2,802.1x		
Operating Condition	Operating Temperature				-30 ~ 65℃		
	Storage Temperature			-50~80°C			
	Humidity			≤95%(non-condensed)			
Product Size	Size:205*205*132.3mm						
	Weight: 0.5kg						



867MBPS ACCESS POINT



PROBE

Packing List	1 Power Supply			
	1 Stainless Steel Fixed Ring			
	1 Pole Bracket			
	1 Bracket Lock			
	1 Wall Hanging			
	4 Screws			
	1 Rubber Plug			
	1 Specification			