



## W-24VAC-9P/10A

### Camera Power Supply



### Model

W-24VAC-9P/10A

### Features

- > Input 110V AC
- > Output 24V DC, 9 channels
- > 10 Amp Supply Current
- > Integral Surge Protection
- > Individual LED Power Indication
- > Individual PTC Output Protection
- > Max. Amp: 1.1Amp/ch



## W-24VAC-9P/10A

### Specifications

Model	W-24VAC-9P/10A	
Specification	240W24V10A9P	
Shape Dimension	28×20.8×8.7cm	
Weight	4.78kg	
Input	Input Voltage	110VAC
	Input Voltage Frequency	60Hz
Output	Output Voltage	24VAC±5%
	Output Current	10A, 9channels for 18sets load
Fuse	Type /Rating	PTC 1.1A/60V
Protection	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when condition removed, then switch back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will open the circuit, when condition removed, PTC fuse will automatically back to close.
Circumstances	Working Temperature	0°C ~ +40°C
	Storage temperature	-20°C ~ +85°C
	RH	5% ~ 95%
	Heat release	Natural heat dissipation
Connection	Input	three-pin socket
	Output	channels output

GSS East (NY Branch)  
59-43 Fresh Meadow Lane  
Fresh Meadows, NY 11365  
718-767-0099

GSS West (CA Branch)  
15222 Stafford St  
City of Industry, CA 91744  
323-234-2835

\*Design and specifications are subject to change without notice.